

PRODUCT CATALOGUE ISSUE 2.0





This guide has been developed with the most innovative products for fire rated applications.

With the inclusion of products from some of the most recognised manufacturers in the fire rated industry, you can be assured that your choice in products has been tested, approved and is right for its application.

For competitive pricing of all products, contact us for our comprehensive price guide and to discuss your needs.

We can also help you plan your site needs with personalised help to make sure you get the right product for the right application.



TABLE OF CONTENTS

Cast in fire collars	04	Fire pillows	18
Cast in fire collars installation	05	Fire rated mortar/grout	18
Cast in fire collars	06	Fireban polyurethane	18
Retrofit fire collars	07	Promashield	19
Retrofit fire collars installation	08	Fixings	20
Blue collars	09	Cable ties	21
Fire wrap & bands	10	Tapes	21
Locks	11	Hollow wall anchors	22
Strapping	11	Fire rating sticker	23
Metal Plates	11	Driver bits	23
Fire rated wrap	12	Drill bits	23
Fire rated damper packing	12	Crayons	24
Rock wool insulation	13	Markers & Paint	25
Fire rated batt	13	Foam Joint	26
Fire rated backer Rod	13	Extinguishers	26
Fire rated board	14	Safety glasses	27
Intumescent fire damper	15	Head protection	27
Firebox	15	Sun Screen	27
Fire sealants	16	Electrolyte drink	27
Caulking & Sausage guns	17	Light duty gloves	27



CAST IN FIRE COLLARS*

CAST IN FIRE COLLAR STACK*



PART NO	SIZE - MM	PACK QTY
22CIC-H50S	40 - 50	24
22CIC-H65S	40 - 65	18
22CIC-H100S	65 - 100	12
22CIC-H150S	150	6



22CIC-200C	200	1
22CIC-250C	250	1
22CIC-315C	315	1



22CIC-H110S 110 1



22CIC-UL100FWS 67 1

CAST IN FIRE COLLAR STACK*



PART NO	SIZE - MM	PACK QTY
LOW PROFILE		
22CIC-L50S	40/50	75
22CIC-L65S	65	24
22CIC-L80S	80	24
22CIC-L100S	65-100	24

CAST IN FIRE COLLAR FLOOR*

Designed for installation in the concrete slab for floor waste and shower - where waste traps are situated below the floor level, flush finish or open on the top side.



PART NO	SIZE - MM	PACK QTY
22CIC-H50FWS	40 - 50	24
22CIC-H65FWS	50 - 65	18
22CIC-H100FWS	65 - 100	12
22CIC-H150FWS	150	6

See page 6 for Low Profile design



CAST IN FIRE COLLARS

INSTALLATION FEATURES

CAST IN FIRE COLLAR INTERNALS

Where a building element is penetrated by a service, fire collars are installed around pipes and other penetrations so that it does not compromise the fire resistance level (FRL) of the building element (wall or floor) the pipes pass through.

Cast in collars are made to be cast into concrete slabs for floorwaste and stack applications. There are important differences between the stack test and the floorwaste test

The Stack Test when tested under laboratory conditions has 2 meters of pipe on the non-fire side and has thermocouples placed in an insulated position on the outside of the pipe, 25mm from the wall or floor. These cast in collars are colour coded white.


The Floorwaste Test, which is more onerous than the Stack test, has thermocouples place on an open part of the grate on the top side of the floor slab. These cast in collars are colour coded black.

The one piece cast in collar is a strong plastic body with extra ribbing to ensure there is sufficient strength prior to and during the concrete pour.

Removable hi-vis yellow lids and patented pipe guides allow for fast installation and are easy to see when installed onto the deck.







INSTALLATION OF CAST IN FIRE COLLARS

Unique cluster testing means you can install your collars closer together providing easier alignment of piping from level to level, simpler layout so compliance is easier to achieve and potential to reduce the service areas.

Collars tested for floorwaste and shower applications are fully tested with a range of pipe types and sizes including PVC, HDPE, VALSIR, DBLUE, PEX, PEX-AL-PEX, RAUPIANO, WAVIN and so on. Many of these tests include testing with fittings fully installed into the fire collar so it is easier to install on site whilst ensuring compliance. Please talk to Drillfast and your certifier to ensure you have the Test Reports and Test Assessments you need to allow you to get the job done.



CAST IN FIRE COLLAR FLOOR*

NASTE & SHOWER



PART NO	SIZE - MM	PACK QTY
LOW PROFILE		
22CIC-L50FWS	40 - 50	75
22CIC-L65FWS	65	24
22CIC-L80FWS	80	24
22CIC-L100FWS	65 - 100	20

See page 4 for High Profile design

CAST IN SHELL

SHFLL

A plastic casing without fire prevention material used for concrete floor penetrations only without fire-rating requirements.



PART NO	SIZE - MM	PACK QTY
22SH50	50	1
22SH65	65	1
22SH100	100	1
22SH150	150	1

EXTENSION TOP

Used for extending height of 22CIC-H100 Collars when casting in thick slabs greater than 250mm thick. Alternatively, use low collars & extend with PVC pipe.



PART NO	SIZE - MM	PACK QTY
22100TOP	100	1
22110TOP	110	1

CAST IN COLLARS VALSIR*



PART NO	SIZE - MM	PACK QTY
STACK ONLY		
22CIC-H50S	40, 50mm Valsir	24
22CIC-L50S	40, 50mm Valsir	75
22CIC-H100S	75, 110mm Valsir	12
22CIC-L100S	75, 110mm Valsir	24
22CIC-H110S	50, 75, 90, 110mm + fittings Valsir	20
22CIC-H150FWS	160mm Valsir	6
FLOORWASTE & SHOWERS		
22CIC-H100FWS	110mm Valsir	12
22CIC-L100FWS	110mm Valsir	24



RETROFIT FIRE COLLARS*

RETROFIT FIRE COLLAR

LOOR WAS LE & SHOWER



PART NO	SIZE - MM	PACK QTY
22RF-LP50R	50	15
22RF-LP80R	65-80	12
22RF-LP100R	100 (PVC)	20





JUMBO RETROFIT FIRE COLLAR



PART NO	SIZE - MM	PACK QTY
22RF-LP200R	200	4
22RF-HP250R	250	1
22RF-HP315R	315	1
22RF-HP400R	400	1

RETROFIT FIRE COLLAR

Surface mounted fire collar for plastic pipework for retro-fit applications.



PART NO	SIZE - MM	PACK QTY
STANDARD		
22RF-32R	16 - 32	50
22RF-50R	40 - 50	40
22RF-63R	65	36
22RF-65-80R	65 - 80	18
22RF-110R	100	20
22RF-150R	150	20

See page 9 & 10 for more options

*It is the responsibility of the installer to ensure compliance. For specific product details and for installation instructions please contact Drillfast.



RETROFIT FIRE COLLARS

INSTALLATION FEATURES



RETROFIT FIRE COLLAR IN ACTION

Building fires are a real concern in every country. Passive fire systems, including the installation of retrofit fire collars, help make it safe for the occupants and emergency personnel, in the event of a fire.

Retrofit fire collars are available in a range of styles and sizes for many application types. Due to the many different applications on site these collars are tested in multiple lab conditions with consideration for wall construction, wall



INSTALLATION OF RETROFIT COLLARS

Retrofit collars are usually installed after the substrate, such as a wall or floor, has been constructed. When installing these collars, it is important to remember that they are installed correctly. Remember:

thickness, hole size, service size and type, fire resistance levels and fixing options.

Due to the many variables with testing and installing retrofit collars the Australian Standard AS1530.4:2014 says, "All Fire Resistance Levels (FRLs) achieved on framed plasterboard wall systems are applicable to concrete and masonry wall of equal or greater thickness" (AS1530.4:2014 Section 1012.2 (c)).

Check the collar has been tested on the matching substrate

Check that the service type and penetration size has also been tested in this application.

Ensure the correct fixings are used for installation

Ensure that the correct fire rated mastic is used on relevant installations for a fully compliant system.

To support the installation, correct documentation is just as critical as the correct installation. Reference documentation may include Test Reports, Test Assessments and Fire Engineering Reports to just name a few. Subject to specific project requirements, you should always make sure you have the most current and up-to-date supporting documentation.





CXL GAS FIRE COLLAR PART NO SIZE · MM PACK QTY 22GAS32 16-32 8 22GAS50 32-50 5 22GAS63 63 1



22WC100





*It is the responsibility of the installer to ensure compliance. For specific product details and for installation instructions please contact Drillfast.

10

UNICOLLAR

PROMAT

A segmented universal firecollar for custom applications. Suitable for up to 100mm pipe diameter.





PIPE WRAPS & BANDS*

FIRE RATED PIPE WRAP

Easy to fit with an adhesive tab, and are unaffected by moisture, humidity or frost but care should be taken so as to avoid damaging the outer polythene sleeve. (To be used in conjunction with a metal band sleeve for hollow walls). Install With Fire Rated Mastic.



PART NO	SIZE - MM	PACK QTY
50PW32	32	10
50PW40	40	10
50PW50	50	10
50PW65	65	10

FIRE RATED P		
PART NO	SIZE - MM	PACK QTY
50PW80	80	10
50PW80	80	10
50PW100W	100 (Wall)	10
50PW100F	100 (Floor)	10
75PW150	150	5

WALL COLLAR BAND			
PART NO	SIZE - MM	SUITS	PACK QTY
22BAND40	54	32/40	10
22BAND50	68	50	10
22BAND65	87	65	10
22BAND80	101	80	10
22BAND100	132	100	10
22BAND150	181	150	10

^{*}It is the responsibility of the installer to ensure compliance. For specific product details and for installation instructions please contact Drillfast.





PART NO	SIZE - MM	QTY
30PADLOCK40003	40mm red 003	1
30PADLOCK4	Padlock set of 4 (keyed alike)	1
30PADLOCK5	Padlock set of 5 (keyed alike)	1
30PADLOCK10	Padlock set of 10 (keyed alike)	1
30PADLOCK30	Padlock set of 30 (keyed alike)	1
30PADLOCK1	Padlock set of 1	1
30PADLOCK2	Padlock set of 2	1
30PADLOCK30C	Combination Padlock 30mm	1











FIRE DAMPER PACKING

4 HR FIRE RATED



PART NO	SIZE - MM	LENGTH - MM	PACK QTY
FIRE DAMPER	R PACKING		
22FDP100	100	3600	5
22FDP150	150	3600	5
22FDP200	200	3600	5
22FDP250	250	3600	5

FIRE RATED WRAP

nstall with Fire Rated Mastic

FyreWrap* is a foil-faced, fire protection wrap/ blanket designed to provide fire rating to ducts, kitchen exhausts, smoke spill systems, penetration seals, structural steel elements. Also provides insulation against metallic penetrations of plasterboard, concrete and masonry walls and floors. For use on services including steel, copper and brass pipes, pipe with combustible insulation, cables with and without cable trays......



PART NO	SIZE - MM	THICKNESS	QTY
FYREWRAP			
22FW450	450 x 7620	38mm	12
22FW610	610 x 7620	38mm	12
22FW/1220	1220 v 7620	38mm	6

FIRE RATED WRAP

nstall with Fire Rated Mastid



PART NO	SIZE - MM	THICKNESS	QTY
ROCK WOOL BLAN	KET		
22RW450FF600	600 x 5000	38	1
22RW450FF1200	1200 x 5000	38	1



PART NO	SIZE - MM	THICKNESS	QTY
FYREPLY PENOWR			
22PENOWRAP	10 x 300	12	1



PROMASEAL SUPAWRAP PROMAT			
PART NO	SIZE - MM	QTY	
22SW	600 x 4000	1	



ROCK WOOL



PART NO	SIZE - MM	LENGTH - MM	PACK QTY
ROCK WOOL INSULA	TION		
22RWSPI2240F	22 x 40	1200	6
22RWSPI2540F	25 x 40	1200	4
22RWSPI3240F	32 x 40	1200	4
22RWSPI3840F	38 x 40	1200	2
22RWSPI5040F	50 x 40	1200	18
22RWSPI6540F	65 x 40	1200	18
22RWSPI7640F	76 x 40	1200	17
22RWSPI10040F	100 x 40	1200	15
22RWSPI11540F	115 x 40	1200	12
22RWSPI13040F	130 x 40	1200	9
22RWSPI17040F	170 x 40	1200	8

ROCK WOOL SUPAWRAP SLEEVE



PART NO	SIZE	QTY
22RWPRO21MM	21mm	14
22RWPRO25MM	25mm	14
22RWPRO32MM	32mm	14

FIRE BATT SUPPORT BRACKET



PART NO	SIZE	QTY
22FBSB90	Z Tag clip 90x30mm	25

FIRE RATED BATT



PART NO	SIZE - MM	THICKNESS	QTY
22NWBB50	1200 x 50	50mm	1
22NWBB60	1000 x 600	60mm	48
22INTUBATT	1200 x 600	50mm	1

BACKER ROD



PART NO	SIZE	PACK QTY
GREEN IBS - PRO	DMAT	
22IBS16	16mm rod x 150m	1
22IBS22	22mm rod x 100m	1
22IBS29	29mm rod x 60m	1
22IBS38	38mm rod x 30m	1
22IBS5020	50 x 20mm strip x 50m	1
22IBS10010	100 x 10mm strip x 50m	1
STANDARD		



BACKER ROD (NOT FIRE RATED)			
20BACKER20 20mm rod x 50m 1			
20BACKER25	25mm rod x 50m	1	
20BACKER30	30mm rod x 50m	1	





PART NO	SIZE - MM	THICKNESS - MM	PACK QTY
MAXILITE™ WHITE			
22MFB30152100	1520 x 1000	30	30
22MFB40152100	1520 x 1000	40	22
22MFB60152100	1520 x 1000	60	15
MAXILITE™ BLUE			
22MFB30204122	2040 x 1220	30	32
22MFB40204122	2040 x 1220	40	25
22MFB60204122	2040 x 1220	60	14
L500BOARD ETEX GROUP			
22FBOARD250050	2500 x 1200	50	1
22FBOARD120050	1200 x 1200	50	1
22FBOARD40050	400 x 400 x 50	50	1
22FBOARD50060050	500 x 600 x 50	50	1
CUSTOM SIZES	Ring to confirm	50	1




FIRE DAMPER GRILLES

INTUMESCENT FIRE DAMPER

SOLIARE AND ROLIND

Intumescent fire damper grilles allow the bi-directional movement of air through firerated walls and floors. When a fire occurs, the intumescent slats in the grille expand rapidly to form a compliant fire barrier. These dampers are easily identified, with foil covered intumescent slats in a rigid steel frame. Installation is quick and easy.



PART NO	SIZE - MM	PACK QTY	
SQUARE			
22IFDIL100100SQ	100 x 100	1	
22IFDIL150150SQ	150 x 150	1	
22IFDIL200200SQ	200 x 200	1	
22IFDIL250250SQ	250 x 250	1	
22IFDIL300300SQ	300 x 300	1	
22IFDIL350350SQ	350 x 350	1	
22IFDIL400400SQ	400 x 400	1	
22IFDIL450450SQ	450 x 450	1	
22IFDIL500500SQ	500 x 500	1	
22IFDIL550550SQ	550 x 550	1	
22IFDIL600600SQ	600 x 600	1	
22IFDIL700700SQ	700 x 700	1	
ROUND			
22IFDIL100360C	100 x 360	1	
22IFDIL125360C	125 x 360	1	
22IFDIL150360C	150 x 360	1	
22IFDIL200360C	200 x 360	1	
22IFDIL250360C	250 x 360	1	
22IFDIL300360C	300 x 360	1	
22IFDIL350360C	350 x 360	1	
22IFDIL400360C	400 x 360	1	
22IFDIL450360C	450 x 360	1	

RECTANGLE		
22IFDIL100150	100 x 360	1
22IFDIL150300	150 x 300	1
22IFDIL200100	200 x 100	1
22IFDIL230100	230 x 100	1
22IFDIL250600	250 x 600	1
22IFDIL300800	300 x 800	1
22IFDIL350550	350 x 550	1
22IFDIL400500	400 x 450	1
22IFDIL450550	450 x 550	1
22IFDIL500600	500 x 600	1
22IFDIL550350	550 x 350	1
22IFDIL600700	600 x 700	1
22IFDIL650150	650 x 150	1
22IFDIL7002400	700 x 2400	1
22IFDIL800200	800 x 200	1
22IFDIL1000900	1000 x 900	1
22IFDIL1100350	1100 x 350	1
22IFDIL1200400	1200 x 400	1
22IFDIL15001000	1500 x 1000	1

Contact us for more sizes

MULTI - SERVICE BOXES

The Multi-Service fire box is an intumescent type product designed for multiple services through various substates

PART NO SIZE - MM PACK QTY



FIREBOX - GREEN		
22BFB150	150 x 150 x 270	1
22BFB300	300 x 150 x 270	1
22BFB550	550 x 150 x 270	1
22BFW300	Boss Fire Wrap 300mm x 1.2 metre	1



FIRE SEALANTS

FIRE SEALANT

UP TO 4 HR FIRE RATING

This fire-rated silicone offers superior qualities combined with excellent movement accommodation, temperature stability, UV resistance and ageing characteristics. It offers excellent resistance to fire to a rating of up to 4 hours.





*it is the responsibility of the installer to ensure compliance. For specific product details and for installation instructions please contact Drillfast.









FIRE RATED FOAM UP TO 4 HR FIRE RATING

Self expanding, ready to use polyurethane foam with propellants, which are completely harmless to the ozone layer. Has a fire rating of up to 4 hours.





CAVITY FILLERS

FIRE PILLOW

UP TO 4 HR FIRE RATING

Up to 4 hour fire resistance. Available in 4 standard sizes. Easy to install. For wall and floor applications. Dust proof - safe for the work environment. Protects cable trays, ducts and other cable penetrations.



PART NO	DESCRIPTION	SIZE - MM	PACK QTY
22PMFPSP	Small - Promat	100 x 250 x 40	30
22PMFPMP	Medium - Promat	200 x 250 x 40	20
22FPMFPLP	Large - Promat	300 x 250 x 40	15
22PMFPXLP	X Large - Promat	600 x 250 x 40	1
22FPSP100	Small	100 x 250 x 30	1
22FPMP200	Medium	200 x 250 x 40	1
22FMLP300	Large	300 x 250 x 40	1
22FMXLP600	X Large	600 x 250 x 40	1

FIREBAN POLYURETHANE

JP TO 4 HR FIRE RATING



PART NO	SIZE	PACK QTY
22FSPU600	600ml	20

FIRE RATED MORTAR/GROUT



PART NO	SIZE	QTY
22FG-20	20kg - Mortar/Grout Promat	64





FYRESET LIGHTWEIGHT



PART NO	SIZE	QTY
22FSET10	10kg - FyreSet lightweight	1

PART NO SIZE QTY 20NSG20 20kg - Non Shrink Grout 1

RAPID SET CONCRETE



PART NO	SIZE	QTY
20RSC20	20kg - Rapid Set Concrete	1



INSULATION ON SERVICES MADE EASY

- Insulation criteria for service penetrations with no wrapping, strapping or taping
- Top side installation only
- Cutting-edge innovative fire protection technology
- A versatile unique retrofit design
- Guaranteed significant savings with onsite time and cost
- System fully fire tested FRL-/120/120 to AS 1530: Part 4

PROMASHIELD			
PART NO	SIZE	QTY	
224069797	Promashield 65	10	
224069998	24069998 Promashield 100		
224069799	Promashield 200	2	



FIXINGS

HEX SCREW BOLT

ZINIC



		MEASUREMENT IN MM			
PART NO	HOLE	DRILL SIZE	LENGTH	FASTENS	PACK QTY
03BT530	5	5	30	5	200

SLEEVE ANCHOR

ZINC



PART NO	SIZE - MM	DRILL SIZE	FASTENS	QTY
01HS10100	10x100	10mm	57mm	50
01HS6525	6.5x25	6.5mm	4mm	100
01HS0840	8x40	8mm	7mm	100
01HS1060	10x60	10mm	20mm	50
01HS10100	10x100	10mm	57mm	50
01HS1275	12x75	12mm	25mm	25

BUGLE HEAD NEEDLEPOINT SCREW



PART NO	SIZE - MM	PACK QTY
09BLAM1040	10g x 38 coarse	1000
09BLAM1050	10g x 50 coarse	1000

PIGTAIL SCREWS



PART NO	SIZE - MM	PACK QTY
22PIG90	900mm	1000

CLOUTS



PART NO	SIZE - MM	PACK SIZE	
10CLPG2028-1	20 x 2.80	1kg	
10CLPG2028-5	20 x 2.80	5kg	
10CLPG2528-1	25 x 2.80	1kg	
10CLPG2528-5	25 x 2.80	5kg	
10CLPG3028-1	30 x 2.80	1kg	
10CLPG3028-5	30 x 2.80	5kg	
10CLPG5028-1	50 x 2.80	1kg	
10CLPG5028-5	50 x 2.80	5kg	

FIRE RATED WEDGE ANCHOR



PART NU	SIZE-MIM	SIZE - MM	- MM	QTY
06PBZ0635	6 x 35	6	4	100







PART NO	SIZE - MM	PACK QTY
152H4	2 - 3	100
154H24	3 - 7	100
154H58	8 - 13	100
154H912	14 - 20	100

CABLE TIES

STAINLESS STEEL

PART NO SIZE - MM PACK QTY



36CT20046SS	200 x 4.6	100
36CT36079SS	360 x 7.9	100
36CT52046SS	520 x 4.6	100
36CT55079SS	550 x 7.9	100
36CT75079SS	750 x 7.9	100
36CT84046SS	840 x 4.6	100
36CT122046SS	1200 x 4.6	100

METAL STRAPPING

14MS12	Steel 12mm x 200	1 roll
14MSC12	Steel Strapping Seals 12	200
14MSTT	Tensioner Tool	1



NYLON		
36CT20046	200 X 4.6	100
36CT28046	280 X 4.6	100
36CT53080	550 X 8.0	100
36CT83090	920 X 9.0	100
36CT122090	1210 X 9.0	100

TAPES

MASKING TAPE



PART NO	COLOUR	SIZE - MM	PACK QTY
21MTAPE	White	25	36
21MTAPE50	White	50	10

ALUMINIUM TAPE

Moisture and vapour barrier for duct systems. Conforms well to corners and irregular surfaces with excellent adhesion properties.



PART NO	SIZE - MM	PACK QTY
21AT50R	50 x 50m	24
21AT72R	72 x 50m	16
21AT96R	96 x 50m	12

DUCT TAPE



PART NO	COLOUR	SIZE - MM	PACK QTY
21DT13G	Grey	0.13 x 48 x 30m	64
21DT13B	Black	0.13 x 48 x 30m	64



HOLLOW WALL ANCHORS





HOLLOW WALL ANCHOR

SETTING TOOL



PART NO DESCRIPTION PACK QTY
07HWAST-200 Jumbo HWA tool 1

HOLLOW WALL ANCHOR

An excellent fixing for higher loads in plasterboard walls and ceilings. Supplied with a crossed pan head screw. Use the setting tool to make light work of the installation of this superior fixing.

PART NO	THREAD SIZE	HOLE - MM	WALL THICKNESS - MM	PACK QTY
07HWA4XS	1/8"	8	4 - 5	100
07HWA4S	1/8"	8	10 - 12	100
07HWA4SL	1/8"	8	3 - 16	100
07HWA4L	1/8"	8	16 - 24	100
07HWA4XL	1/8"	8	32 - 36	50
07HWA6S	3/16"	10	10 - 16	50
07HWA8S	1/4"	11	10 - 12	50



SDS DRILL BIT

SDS plus suits all Rotary Hammers. Quality high grade alloy steel ensures strength and durability.



PART NO	SIZE - MM	WORKING LENGTH
24S05110	5 x 110	50
24S05160	5 x 160	100
24S06110	6 x 110	50
24S06160	6 x 160	100
24S065110	6.5 x 110	50
24S065160	6.5 x 160	100
24S10160	10 x 160	100
24S10210	10 x 210	150
24S12160	12 x 160	100
24S12210	12 x 210	150

FIRE RATING STICKER



PART NO	DESCRIPTION	PACK QTY
22FRS	Penetration sticker	250
22TRS- CUSTOM	Custom penetration sticker	please ring
22FRSD- CUSTOM	Customer damper sticker	please ring

SCREWD	RIVER BITS	
PART NO	SIZE	PACK QTY

PHILLIPS BITS				
25PH25	No2 x 25mm Insert	10		
25PH50	No.2 x 50mm	10		
25PH75	No.2 x 75mm	10		
25PH100	No.2 x 100mm	10		
25PH150	No.2 x 150mm	10		
25PH45	No.2 x 45 D/End	10		
25PH65	No.2 x 65 D/End	10		
25PH2+SL6	No.2 + SL x 45mm	10		
SQUARE DRIVE				
25SQ225	No.2 x 25mm	10		
POZI DRIVE				
25PZ2	No.2 x 25mm	10		
25PZ3	No.3 x 25mm	10		
TORX				
25TX40	TORX 40 x 25mm	10		
HEX BIT				
25H5	5 x 30mm Internal	10		

TAPE MEASURE



PART NO	DESCRIPTION
39889TM	8mtr







Refill 4oz - Blue

Refill 4oz - Yellow

Refill 6oz - Black

Reel 30m

6

6

6

29CR004B

29CR004Y

29LCR30

29CR006-BLK



PERMANENT MARKERS



PART NO	DESCRIPTION	PACK QTY
29PM-BLK	Black Permanent	36
29N50IZ	Black Inkzall Perm. Fine Point	1
29N50IZC	Black Inkzall Perm. Chisel Tip	1
29N50IZM	Black Inkzall Perm. Medium Point	1

PAINT MARKER



PART NO	COLOUR	PACK QTY
29UNIWH	White	12
29UNIY	Yellow	12
29UNIBL	Black	12
29UNIB-NS	Blue	12
29UNIR-NS	Red	12
29UNIG-NS	Green	12

SPOT MARKING PAINT



PART NO	COLOUR	SIZE	PACK QTY
29APSMW	White	350g	12
29APSMB	Blue	350g	12
29APSMY	Yellow	350g	12
29APSMR	Red	350g	12
29APSMFO	FL Orange	350g	12
29APSMFP	FL Pink	350g	12
29APSMFG	FL Green	350g	12





PART NO	DESCRIPTION	PACK QTY
22FEXT-1	Fire Extinguisher 1kg ABE	1
22FEXT-2	Fire Extinguisher 2kg ABE	1
22FEXT-45-NS	Fire Extinguisher 4.5kg ABE	1
22FEXT-9-NS	Fire Extinguisher 9kg ABE	1







PROTECTION EQUIPMENT





PART NO	DESCRIPTION	PACK QTY
27HDHT	Hard Hat Vented	1
27HDHTSV	Hard Hat Sun Visor	1
27HCCS	Chin Strap	1
27HCSB	Sweatband	1
27HHELC	Hard Hat Elastic Lanyard Clamp 3155	Each
27SGL	Lanyard for Safety Glasses	Each





LIGHT DUTY GLOVES

Light duty gloves for general use.



