



THREADED ROD



THREADED ROD - MINIMUM PROOF LOAD (KN)

Code		Nominal Size	Pitch mm	Stress Area mm ²	Class 4.6
Zinc plated	Hot Dip Galv				
13TRM063	13TRM063G	M6	1.00	20.10	4.52
13TRM083	13TRM083G	M8	1.25	36.60	8.24
13TRM103	13TRM103G	M10	1.50	58.00	13.10
13TRM123	13TRM123G	M12	1.75	84.30	19.00
13TRM163	13TRM163G	M16	2.00	157.00	35.30
13TRM203	13TRM203G	M20	2.50	245.00	55.10
13TRM243	13TRM243G	M24	3.00	353.00	79.40

THREADED ROD MINIMUM ULTIMATE TENSILE LOAD (KN)

Code		Nominal Size	Pitch mm	Stress Area mm ²	Class 4.6
Zinc plated	Hot Dip Galv				
13TRM063	13TRM063G	M6	1.00	20.10	8.04
13TRM083	13TRM083G	M8	1.25	36.60	14.60
13TRM103	13TRM103G	M10	1.50	58.00	23.20
13TRM123	13TRM123G	M12	1.75	84.30	33.70
13TRM163	13TRM163G	M16	2.00	157.00	62.80
13TRM203	13TRM203G	M20	2.50	245.00	98.00
13TRM243	13TRM243G	M24	3.00	353.00	141.20